

<u>COMMERCIAL VESSEL</u>	<u>16 - UNDER 26 FT / 26 - UNDER 40 FT</u>
---------------------------------	---

Vessels > 5 net tons (approx 25') must be Documented "Coastwise" & endorsed for "6 passengers or less"

CG DOCUMENTATION

STATE NUMBERING	3 inch Block, contrasting color, forward half of vessel. NOT REQUIRED IF CG DOCUMENTED
CERTIFICATE OF NUMBERS	Valid State certificate whenever underway. Temp and official duplicate accepted (No Photocopy) NOT REQUIRED IF CG DOCUMENTED
DOCUMENTATION / DISPLAY	Document on board, original, current. Name 4" on both sides of bow. Name and Hailing port on stern
OFFICIAL NUMBER	3" Minimum, permanently affixed to an integral, interior structural member. NOT REQUIRED IF STATE NUMBERED.
OPERATORS LICENSE	A Licensed operator/master is required for: All inspected vessels; or All uninspected passenger vessels. If required current, valid, readily available.
PFD	One type I, II, III, or V for each POB. Type I if carrying passengers for hire. PML required for Great Lakes voyages. Wearable must have 200 sq. cm retro front and back.
RING BUOY	<u>26 - UNDER 40 FT-</u> One ring buoy 20 inches or larger, CG approved, immediately available
EPIRB	Not required for uninspected passenger vessels under 100 GT
SOUND PRODUCING DEVICE	Some means of making efficient sound signal, audible for 1/2 NM
FIRE EXTINGUISHER	<u>16 - UNDER 26 FT-</u> One B-I when closed construction or carrying passenger for hire. <u>26 - UNDER 40 ft-</u> One B-II or two B-I; Fixed system = one B-I
FLAME CONTROL	Required on gasoline engines installed after 25 apr 1940, except outboards
VENTILATION	Gas engines and storage areas on vessels built after 25 apr 1940 - Natural ventilation (cowling, ducts). Vessels after 31 jul 1980 - Must have rated power exhaust blower and label next to ignition.
NAVIGATION / ANCHOR LIGHTS	Sunset to Sunrise and restricted visibility
MARINE SANITATION DEVICE	If installed toilet: Type I, II, or III, Y-valve closed to prevent direct overboard discharge within 3 nm of baseline
VISSUAL DISTRESS SIGNALS	Any combination of these: - One day NON-PYRO and one night NON-PYRO, or - Three day PYRO and one night NON-PYRO, or - Three combination day/night PYRO.

OIL POLLUTION PLACARD	26 - UNDER 40 FT- Posted in machinery space or next to bilge pump controls
OIL POLLUTION	Capacity to retain on board all Oily mixtures. Equipped to discharge these oily mixture to a reception facility. Fixed or portable means of removal is acceptable.
GARBAGE PLACARD	Conspicuously posted
NAVIGATION RULES BOOK	Required on inland waters if 39' 4" or over